

Technical Data Sheet





- · Comprehensive range available.
- Fast starting, single self tapping spaced thread.
- Suitable for Plastic, timber and thin sheet metal.
- Effective for unreinforced PVCU window and door manufacture.
- Ideal for attaching hardware to PVCu Profile.

Technical Specifications

DETAIL	DESCRIPTION			
Designed For	Attaching hardware to unreinforced PVCu and multi-chamber profile			
Head Style/Drive Recess	Countersunk - Phillips PH2			
Thread Form/Point	Single Deep Thread – Fast Starting Gimlet Point			
Effective Thread Length	Fully Threaded			
Material Grade	AISI C1018/C1022 Carbon Steel - Case Hardened			
Coating	Electroplated Zinc Yellow (Y)	Electroplated Zinc Clear (Z)		
Corrosion Protection	Grade 4 acc. to BS EN 1670:2007			
Salt Spray Test (SST)	Minimum 240 Hours in accordance with BS EN ISO 9227:2022+A1:2024			

Mechanical Data - Average Resistance Characteristics

NOMINAL SIZE	RECOMMENDED TENSILE CAPACITY (F _t swL)	RECOMMENDED SHEAR LOAD $(F_{_{\!$	TENSILE STRENGTH (RM)	RECOMMENDED TORSIONAL CAPACITY (F1,swl)
CFG 4.0mm	1.86 kN	1.1 kN	324 MPa	1.01 Nm
CFG 4.3mm	2.04 kN	1.2 kN	324 MPa	1.16 Nm
CFG 4.8mm	2.81 kN	1.7 kN	324 MPa	1.87 Nm

NOTE Data values are based on single-point tests and calculations and are indicative only. Specifiers, end-users, and third parties are responsible for determining and applying appropriate safety factors, not exceeding the stated average resistance characteristics or the limitations of the application.

Installation Guidance

For optimal performance and compliance, thorough user-specific testing to validate the product's suitability for the intended design or application is strongly recommended. Such testing should consider variables such as material compatibility, load requirements, environmental conditions, and installation methods.

- Impact-type electric drills/drivers are not recommended for fixing screws into PVCu windows and doors due to the high-torque, percussive action they generate.
- Percussive action can cause material micro-cracks or stress fractures.
- Excessive torque can strip screw threads or damage the PVCu material, reducing joint integrity.
- · Inconsistent torque application results in uneven or insecure screw installation, weakening the fixing.
- High-speed impacts can wear away protective coatings, increasing the risk of corrosion.
- Controlled torque screwdrivers or drills with torque-limiting settings are recommended for optimal performance and durability.

Rapierstar disclaims any liability for misuse, improper installation, or failure to adhere to recommended practices and local building regulations. Additionally, all installations must comply with relevant standards and codes specific to the application, including (but not limited to) those pertaining to safety, structural integrity, and environmental considerations.






Rapierstar Limited Star Business Park, Macclesfield, Cheshire SK11 9JA Tel: +44(0)1260 223311 Fax: +44(0)1260 223399 email: sales@rapierstar.com

www.rapierstar.com





Technical Data Sheet



CFG Product Range

PRODUCT CODE	SIZE – SHANK X NL	HD	н	BOX QUANTITY
CFG 4.0 X 25 Z	4.0mm x 24.0mm	6.75mm± 0.25mm	3.5mm	1000
CFG 4.3 X 13 Z	4.3mm x 13.0mm	7.25mm± 0.25mm	3.0mm	1000
CFG 4.3 X 16 Y/Z	4.3mm x 16.0mm	7.25mm± 0.25mm	3.0mm	1000
CFG 4.3 X 20 Y/Z	4.3mm x 20.0mm	7.25mm± 0.25mm	3.0mm	1000
CFG 4.3 X 22 Y/Z	4.3mm x 22.0mm	7.25mm± 0.25mm	3.0mm	1000
CFG 4.3 X 25 Y/Z	4.3mm x 25.0mm	7.25mm± 0.25mm	3.0mm	1000
CFG 4.3 X 28 Z	4.3mm x 28.0mm	7.25mm± 0.25mm	3.0mm	1000
CFG 4.3 X 30 Y/Z	4.3mm x 30.0mm	7.25mm± 0.25mm	3.0mm	1000
CFG 4.3 X 35 Y/Z	4.3mm x 35.0mm	7.25mm± 0.25mm	3.0mm	1000
CFG 4.3 X 40 Y/Z	4.3mm x 40.0mm	7.25mm± 0.25mm	3.0mm	1000
CFG 4.3 X 45 Y/Z	4.3mm x 45.0mm	7.25mm± 0.25mm	3.0mm	500
CFG 4.3 X 55 Y/Z	4.3mm x 55.0mm	7.25mm± 0.25mm	3.0mm	500
CFG 4.3 X 65 Y/Z	4.3mm x 65.0mm	7.25mm± 0.25mm	3.0mm	500
CFG 4.8 X 25 Y/Z	4.8mm x 25.0mm	6.75mm± 0.25mm	3.0mm	1000
CFG 4.8 X 38 Y/Z	4.8mm x 38.0mm	6.75mm± 0.25mm	3.0mm	500
CFG 4.8 X 45 ZH	4.8mm x 25.0mm	6.75mm± 0.25mm	3.0mm	500
CFG 4.8 X 70 ZH	4.8mm x 25.0mm	6.75mm± 0.25mm	3.0mm	200

Supporting Documentation

- Declaration of Performance: 001CPR01-03-2013-StarPVCU-Carbon-DoP
- ISO9001-2015-218503 BAB Management Certificate
- ISO14001-2015-241585 BAB Management Certificate

Referenced Standards

- BS EN 1670:2007
- BS EN ISO 9227:2022+A1:2024
- BS EN 14566:2008+A1:2009
- ISO 898-1
- ISO 6895-1
- BS 7412:2024





Rapierstar Limited Star Business Park, Macclesfield, Cheshire SK11 9JA Tel: +44(0)1260 223311 Fax: +44(0)1260 223399 email: sales@rapierstar.com

www.rapierstar.com

