



Designed for:	Attaching Hardware to Reinforced Profile
Head Style:	Countersunk
Drive Bit:	PH2
Thread Form:	Spaced Self-Tapping
Point:	Drill Point
Coating:	Electroplated Yellow or Zinc plus Passivation
Salt Spray Testing:	Minimum 250 Hours in accordance with BS EN 9227:2012
Corrosion Protection:	Grade 4 acc. to BS EN 1670:2007
Shank Material:	Carbon Steel
Material Grade:	AISI C1022
Effective Thread Length:	Fully Threaded

Product Code	Size – Shank x NL	HD	Box Quantity
CSR 3.9 x 13 Y or Z	3.9mm x 13.0mm	7.25mm ± 0.25mm	1000
CSR 3.9 x 16 Y or Z	3.9mm x 16.0mm	7.25mm ± 0.25mm	1000
CSR 3.9 x 19 Y or Z	3.9mm x 19.0mm	7.25mm ± 0.25mm	1000
CSR 3.9 x 22 Y or Z	3.9mm x 22.0mm	7.25mm ± 0.25mm	1000
CSR 3.9 x 25 Y or Z	3.9mm x 25.0mm	7.25mm ± 0.25mm	1000
CSR 3.9 x 29 Y or Z	3.9mm x 29.0mm	7.25mm ± 0.25mm	1000
CSR 3.9 x 32 Y or Z	3.9mm x 32.0mm	7.25mm ± 0.25mm	1000
CSR 3.9 x 38 Y or Z	3.9mm x 38.0mm	7.25mm ± 0.25mm	1000
CSR 3.9 x 45 Y or Z	3.9mm x 45.0mm	7.25mm ± 0.25mm	1000
CSR 4.8 x 25 Y or Z	4.8mm x 25.0mm	9.25mm ± 0.25mm	1000
CSR 4.8 x 32 Z	4.8mm x 32.0mm	9.25mm ± 0.25mm	1000
CSR 4.8 x 38 Y or Z	4.8mm x 38.0mm	9.25mm ± 0.25mm	1000
CSR 4.8 x 45 Z	4.8mm x 25.0mm	9.25mm ± 0.25mm	1000
CSR 4.8 x 50 Z	4.8mm x 50.0mm	9.25mm ± 0.25mm	1000
CSR 4.8 x 60 Z	4.8mm x 60.0mm	9.25mm ± 0.25mm	1000



Rapierstar Limited  
Star Business Park, Macclesfield, Cheshire SK11 9JA  
Tel: +44(0)1260 223311 Fax: +44(0)1260 223399  
email: [info@rapierstar.com](mailto:info@rapierstar.com)

[www.rapierstar.com](http://www.rapierstar.com)

