

# **Technical Data Sheet**

# **CSR Carbon Range Window Screw**





- The most comprehensive selection of screws for PVCu fenestration fabrication.
- Specially engineered drill points, thread profile, and head design improve efficiency and ease of use.
- Precision Thread Technology Fast-starting for optimal engagement and reduced insertion torque.
- Effective for steel reinforced PVCu window and door manufacture.

### **Technical Specifications**

DETAIL	DESCRIPTION			
Designed For	Attaching hardware to steel and aluminium reinforced multi-chamber profile			
Head Style/Drive Recess	Countersunk - Phillips PH2			
Thread Form/Point	Spaced Self-Tapping – Self Drilling Point			
Effective Thread Length	Fully Threaded			
Material Grade	AISI C1022 Carbon Steel - Case Hardened			
Coating	Electroplated Zinc Yellow (Y)	Electroplated Zinc Clear (Z)		
<b>Corrosion Protection</b>	Grade 4 acc. to BS EN 1670:2007			
Salt Spray Test (SST)	Minimum 240 Hours in accordance with BS EN ISO 9227:2022+A1:2024			

#### **Mechanical Data - Average Resistance Characteristics**

NOMINAL SIZE	RECOMMENDED TENSILE CAPACITY (F <sub>t</sub> swL)	RECOMMENDED SHEAR LOAD $(F_{_{\!$	TENSILE STRENGTH (RM)	RECOMMENDED TORSIONAL CAPACITY (Ft,swl)
CSR 3.9mm	2.15 kN	1.29 kN	324 MPa	1.26 Nm
CSR 4.2mm	2.49 kN	1.50 kN	324 MPa	1.57 Nm
CSR 4.8mm	3.26 kN	1.95 kN	324 MPa	2.35 Nm

**NOTE** Data values are based on single-point tests and calculations and are indicative only. Specifiers, end-users, and third parties are responsible for determining and applying appropriate safety factors, not exceeding the stated average resistance characteristics or the limitations of the application.

#### **Installation Guidance**

For optimal performance and compliance, thorough user-specific testing to validate the product's suitability for the intended design or application is strongly recommended. Such testing should consider variables such as material compatibility, load requirements, environmental conditions, and installation methods.

- Impact-type electric drills/drivers are not recommended for fixing screws into PVCu windows and doors due to the high-torque, percussive action they generate.
- Percussive action can cause material micro-cracks or stress fractures.
- Excessive torque can strip screw threads or damage the PVCu material, reducing joint integrity.
- Inconsistent torque application results in uneven or insecure screw installation, weakening the fixing.
- High-speed impacts can wear away protective coatings, increasing the risk of corrosion.
- Controlled torque screwdrivers or drills with torque-limiting settings are recommended for optimal performance and durability.

Rapierstar disclaims any liability for misuse, improper installation, or failure to adhere to recommended practices and local building regulations. Additionally, all installations must comply with relevant standards and codes specific to the application, including (but not limited to) those pertaining to safety, structural integrity, and environmental considerations.






Rapierstar Limited
Star Business Park, Macclesfield, Cheshire SK11 9JA
Tel: +44(0)1260 223311 Fax: +44(0)1260 223399
email: sales@rapierstar.com

www.rapierstar.com





# **Technical Data Sheet**



# **CSR Product Range**

PRODUCT CODE	SIZE – SHANK X NL	HD	н	BOX QUANTITY
CSR 3.9 X 16 Y or Z	3.9mm x 16.0mm	7.25mm± 0.25mm	2.85mm	1000
CSR 3.9 X 19 Y or Z	3.9mm x 19.0mm	7.25mm± 0.25mm	2.85mm	1000
CSR 3.9 X 22 Y or Z	3.9mm x 22.0mm	7.25mm± 0.25mm	2.85mm	1000
CSR 3.9 X 25 Y or Z	3.9mm x 25.0mm	7.25mm± 0.25mm	2.85mm	1000
CSR 3.9 X 29 Y or Z	3.9mm x 29.0mm	7.25mm± 0.25mm	2.85mm	1000
CSR 3.9 X 32 Y or Z	3.9mm x 32.0mm	7.25mm± 0.25mm	2.85mm	1000
CSR 3.9 X 38 Y or Z	3.9mm x 38.0mm	7.25mm± 0.25mm	2.85mm	1000
CSR 3.9 X 45 Y or Z	3.9mm x 45.0mm	7.25mm± 0.25mm	2.85mm	500
CSR 4.2 X 45 Z	4.2mm x 45.0mm	7.95mm± 0.15mm	3.15mm	500
CSR 4.2 X 50 Z	4.2mm x 50.0mm	7.95mm± 0.15mm	3.15mm	500
CSR 4.2 X 55 Z	4.2mm x 55.0mm	7.95mm± 0.15mm	3.15mm	500
CSR 4.2 X 65 Z	4.2mm x 65.0mm	7.95mm± 0.15mm	3.15mm	500
CSR 4.8 X 25 Z	4.8mm x 25.0mm	9.25mm± 0.25mm	3.50mm	1000
CSR 4.8 X 38 Y or Z	4.8mm x 38.0mm	9.25mm± 0.25mm	3.50mm	500
CSR 4.8 X 45 Z	4.8mm x 45.0mm	9.25mm± 0.25mm	3.50mm	500
CSR 4.8 X 50 Z	4.8mm x 50.0mm	9.25mm± 0.25mm	3.50mm	500
CSR 4.8 X 60 Z	4.8mm x 60.0mm	9.25mm± 0.25mm	3.50mm	500
CSR 4.8 X 70 Z	4.8mm x 70.0mm	9.25mm± 0.25mm	3.50mm	200

# **Supporting Documentation**

- Declaration of Performance: 001CPR01-03-2013-StarPVCU-Carbon-DoP
- ISO9001-2015-218503 BAB Management Certificate
- ISO14001-2015-241585 BAB Management Certificate

## **Referenced Standards**

- BS EN 1670:2007
- BS EN ISO 9227:2022+A1:2024
- BS EN 14566:2008+A1:2009
- BS 7412:2024





**Rapierstar Limited** Star Business Park, Macclesfield, Cheshire SK11 9JA Tel: +44(0)1260 223311 Fax: +44(0)1260 223399 email: sales@rapierstar.com

www.rapierstar.com

