



Designed for:	Attaching Friction Stays to Unreinforced PVCU
Head Style:	Low Profile Shallow Pan with Braking Serrations
Drive Bit:	PH2
Thread Form:	Single Deep Thread
Point:	Fast Starting Gimlet
Coating:	None
Salt Spray Testing:	1000 Hours in accordance with BS EN 9227:2012
Corrosion Protection:	Grade 5 acc. to BS EN 1670:2007
Shank Material:	Austenitic Stainless Steel
Material Grade:	302
Effective Thread Length:	Fully Threaded

Product Code	Size – Shank x NL	HD	Box Quantity
LFG 4.3 x 16 S	4.3mm x 16.0mm	8.10mm ± 0.20mm	1000
LFG 4.3 x 20 S	4.3mm x 20.0mm	8.10mm ± 0.20mm	1000
LFG 4.3 x 25 S	4.3mm x 25.0mm	8.10mm ± 0.20mm	1000
LFG 4.8 x 16 S	4.8mm x 16.0mm	8.10mm ± 0.20mm	1000
LFG 4.8 x 20 S	4.8mm x 20.0mm	8.10mm ± 0.20mm	
LFG 4.8 x 25 S	4.8mm x 25.0mm	8.10mm ± 0.20mm	
LFG 4.8 x 30S	4.8mm x 30.0mm	8.10mm ± 0.20mm	



Rapierstar Limited
Star Business Park, Macclesfield, Cheshire SK11 9JA
Tel: +44(0)1260 223311 Fax: +44(0)1260 223399
email: info@rapierstar.com

www.rapierstar.com

