



| | |
|-----------------------------------|---|
| Designed for: | Attaching Friction Stays to Reinforced PVCU |
| Head Style: | Shallow Pan with Locking Serrations |
| Recess: | Combination SQ1/PH2 |
| Drive Bit - (Installation): | SQ1 |
| Drive Bit - (On-Site Adjustment) | PH2 |
| Thread Form: | Self-Tapping |
| Point: | Drill Point |
| Coating: | Inorganic Anti-Corrosion Coating |
| Salt Spray Testing (Shank): | 1000 Hours Minimum in accordance with BS EN 9227:2012 |
| Salt Spray Testing: (Drill Point) | 250 Hours Minimum in accordance with BS EN 9227:2012 |
| Corrosion Protection | Grade 5 acc. to BS EN 1670:2007 |
| Shank Material: | Austenitic Stainless Steel |
| Drill Point Material: | Carbon Steel |
| Material Grade: (Shank) | 302 |
| Material Grade: (Drill Point) | AISI C1022 |
| Effective Thread Length: | Fully Threaded |

| Product Code | Size – Shank x NL | HD | Box Quantity |
|-----------------|-------------------|-----------------|--------------|
| SSR 4.5 x 16 CB | 4.5mm x 16.0mm | 8.10mm ± 0.20mm | 1000 |
| SSR 4.5 x 18 CB | 4.5mm x 18.0mm | 8.10mm ± 0.20mm | 1000 |
| SSR 4.5 x 25 CB | 4.5mm x 25.0mm | 8.10mm ± 0.20mm | 1000 |
| SSR 4.5 x 29 CB | 4.5mm x 29.0mm | 8.10mm ± 0.20mm | 1000 |



Rapierstar Limited
Star Business Park, Macclesfield, Cheshire SK11 9JA
Tel: +44(0)1260 223311 Fax: +44(0)1260 223399
email: info@rapierstar.com

www.rapierstar.com

