



Designed for:	Baypole Assembly
Head Style:	Wafer Head
Drive Bit:	PH2
Thread Form:	Twin Self-Tapping Thread with Sprue Clearance Channel
Point:	Drill Point
Coating:	Electroplated Zinc plus Passivation
Salt Spray Testing:	Minimum 250 Hours in accordance with BS EN 9227:2012
Corrosion Protection:	Grade 4 acc. to BS EN 1670:2007
Shank Material:	Carbon Steel
Material Grade:	AISI C1022
Effective Thread Length:	Up to 80mm Fully Threaded. 95mm and above Partially Threaded

Product Code	Size – Shank x NL	HD	Box Quantity
WSR 4.8 x 50 Z	4.8mm x 50.0mm	12.55mm± 0.15mm 200	200
WSR 4.8 x 60 Z	4.8mm x 60.0mm	12.55mm± 0.15mm 200	200
WSR 4.8 x 70 Z	4.8mm x 70.0mm	12.55mm± 0.15mm 200	200
WSR 4.8 x 80 Z	4.8mm x 80.0mm	12.55mm± 0.15mm 200	200
WSR 4.8 x 95 Z	4.8mm x 95.0mm	12.55mm± 0.15mm 200	200
WSR 4.8 x 100 Z	4.8mm x 100.0mm	12.55mm± 0.15mm 200	200



Rapierstar Limited
Star Business Park, Macclesfield, Cheshire SK11 9JA
Tel: +44(0)1260 223311 Fax: +44(0)1260 223399
email: info@rapierstar.com

www.rapierstar.com

