



<b>Designed for:</b>	Fixing decking boards. Suitable for use with ACQ treated timber
<b>Head Style:</b>	Reduced size bugle head with countersinking ribs for extra neat finish
<b>Drive Bit:</b>	Torx T20
<b>Thread Form:</b>	Single thread with pentagonal starform cutting portion
<b>Point:</b>	Fast starting sharp point
<b>Coating:</b>	Zinc plated plus high performance ceramic coating
<b>Salt Spray Testing:</b>	500 Hours in accordance with BS EN 9227:2012
<b>Corrosion Protection:</b>	Grade 5 acc. to BS EN 1670:2007
<b>Shank Material:</b>	Carbon steel
<b>Material Grade:</b>	AISI C1018/1022
<b>Effective Thread Length:</b>	Partially threaded

### BTP Decking Screw Range

Product Code	Size – Shank x NL	HD	Box Quantity
BTP 4.2 x 50 G	4.2mm x 50mm	8.125mm ± 0.255mm	200
BTP 4.2 x 65 G	4.2mm x 65mm	8.125mm ± 0.255mm	200
BTP 4.2 x 75 G	4.2mm x 75mm	8.125mm ± 0.255mm	200
BTP 4.2 x 90 G	4.2mm x 90mm	8.125mm ± 0.255mm	200
BTP 4.2 x 100 G	4.2mm x 100mm	8.125mm ± 0.255mm	200



Rapierstar Limited  
Star Business Park, Macclesfield, Cheshire SK11 9JA  
Tel: +44(0)1260 223311 Fax: +44(0)1260 223399  
email: [info@rapierstar.com](mailto:info@rapierstar.com)

[www.rapierstar.com](http://www.rapierstar.com)

